



# Incubators



The company's production of high precision and quality incubators is suitable for most applications, the company offers a wide range of different models in the capacity and accessories to meet the needs of a large segment of users.



## Laboratory Hot Incubator

### Features:

- ✦ Easy to use analog control unit.
- ✦ Designed for general laboratory use.
- ✦ Provided with two removable chrome plated wire grid shelves.
- ✦ Gravity convection.
- ✦ Easy to maintenance.
- ✦ Protection by fuse.

### Technical Specifications

- ✦ Analogue temperature gauge.
- ✦ Mechanical thermometer to monitor temperature levels.
- ✦ Temperature range from 5°C above ambient Temp. to 60°C .
- ✦ Temperature accuracy  $\pm 1^\circ\text{C}$  .
- ✦ Temperature constancy, temporal  $\pm 2\%$  .
- ✦ Heating light indicator.
- ✦ Stainless steel chamber .
- ✦ Clear view of the chamber through large glass window.
- ✦ Main body made from antirust antibacterial painted sheet steel.
- ✦ Electrical supply 220V / 50Hz.
- ✦ Available models: 10, 20, 35, 50 and 100 Liters.
- ✦ Special specifications and capacities are available upon request as a special order.
- ✦ Stainless steel external body model is available.



Model	BT 1010	BT 1020	BT 1220	BT 1050	BT 1070
Capacity	10 L	20 L	20 L	50 L	100 L
Material	Coated steel	Coated steel	Stainless steel	Coated steel	Coated steel
Internal Dimensions (cm):	24x21.5x20	34x25x28	34x25x28	50x33x35	50x50x50
External Dimensions (cm):	32x41x30	42x45x38	56x39x37	71x50x46	77x62x62
Power (watt)	100 w	100 w	100 w	250 w	500 w
Shelf Positions	2	2	2	3	4