

Tx Series Touch Screen



Features

- 5 inch LCD touch screen with backlight
- Electromagnetic Force Balance Sensor
- mg/g/ct/oz/lb/gn/ozt/dwt/dr/mm/tmr/tar/tl.l/tl.t/tl.h
- Cast aluminum, 3 glass wind-resistant doors, stainless steel weighing pan and surrounding area
- Internal or external calibration
- Print, Counting, Tare, Unit conversion, Auto-calibration, Overload/Error Indication, Percentage/Density/Powder weighing, Time setting
- Power:100-240v(AC)
- RS232 interface

Model	W2002A
Pan Size	Round Pan 90 mm
Capacity	220 g
Resolution	0.0001g
Repeatability	±0.0003g
Linearity Error	±0.0003g
Response Time	≤ 4 sec (can be adjusted)
Calibration	external calibration
Weighing Units	mg/g/ct/oz/lb/gn/ozt/dwt/dr/mm/tmr/tar/tl.l/tl.t/tl.h)
Construction	Cast aluminum, static resistant ABS, static-resistant doors, stainless steel pan
Display	5 inch LCD touch screen with backlight
Body dims	360 x 220 x 320 mm (L x W x H)
Power	110v - 240v, 50HZ / 60HZ
Operat. Temp.	20±2.5°C
Connectivity	Configurable RS 232 interface