



Incubators



The company's production of high precision and quality incubators is suitable for most applications, the company offers a wide range of different models in the capacity and accessories to meet the needs of a large segment of users.



Digital Laboratory Hot Incubator

Features:

- ✦ PID Microprocessor digital controller with large 4-digit display.
- ✦ Built- in calibration.
- ✦ Designed for general laboratory use.
- ✦ Provided with two removable chrome plated wire grid shelves
- ✦ Accuracy in setting and measuring temperature
- ✦ Gravity convection .
- ✦ Protection by fuse .

Technical Specifications

- ✦ PID Microprocessor digital controller with large 4-digit display.
- ✦ Temperature range from 5° above ambient Temp. to 60°C.
- ✦ Accuracy $\pm 0.1^{\circ}\text{C}$.
- ✦ Temperature uniformity $\pm 0.5^{\circ}\text{C}$.
- ✦ Temperature Stability $\pm 0.5^{\circ}\text{C}$.
- ✦ Stainless steel chamber.
- ✦ Clear view of the chamber through large glass window.
- ✦ Main body made from antirust antibacterial painted steel sheet.
- ✦ Provided with removable chrome plated wire grid shelves.
- ✦ Protection by fuse.
- ✦ Electrical supply 220V / 50Hz.
- ✦ Available models: 20, 35, 50 and 100 Liters.
- ✦ Special specifications and capacities are available upon request.
- ✦ Stainless steel external body model is available.



Model	BT 1120	BT 1320	BT 1150	BT 1170
Capacity	20 L	20 L	50 L	100 L
Material	Coated steel	Stainless steel	Coated steel	Coated steel
Internal Dimensions (cm):	34x27.5x25	34x27.5x25	50x33x35	50x50x50
External Dimensions (cm):	56x40x35	56x39x37	71x50x46	77x62x62
Power (watt)	100 w	100 w	250 w	500 w
Shelf Positions	2	2	3	4