

PA 50

Specific Protein Analyzer



Application	Parameters	Sample Type	Linear Range
Inflammation Monitoring	CRP	Whole blood/serum	3-300mg/L
Cardiovascular Diseases	HS-CRP	Whole blood/serum	0.25-20mg/L
Rheumatism Monitoring	Anti-CCP	Serum	5-100IU/L
	RF	Serum/plasma	3-160IU/mL
	ASO	Serum/plasma	20-800IU/mL
Diabetes Monitoring	HbA1c	Whole blood	2-15%
Renal Function Monitoring	CYS-C	Serum/plasma	0-8mg/L
	mALB	Urine	10-200mg/L
Clotting Monitoring	D-Dimer	Plasma	0-20mg/L
	IgG	Serum/plasma	2-40g/L
Immunological Diseases	IgA	Serum/plasma	0.4-8g/L
	IgM	Serum/plasma	0.05-5g/L
	C3	Serum/plasma	0.04-4.5g/L
	C4	Serum/plasma	0.015-2g/L

Tests/Kit: 25T/2×25T/50T/100T

PA 50

Specific Protein Analyzer

PA 50

Specific Protein Analyzer




General Features

- 5.6-inch color touch screen
- Calibration by magnetic card
- Disposable cuvette, no carryover
- Can be extended more than 30 parameters
- Support LIS and barcode
- Less and easy maintenance


Parameter	Ingredient				
	Buffer	Diluent	Latex	Sample	Anti-serum
CRP	600μL	-----	-----	2μL	60μL
HS-CRP	600μL	-----	-----	2μL	60μL
HbA1c	-----	1000μL	300μL	20μL	100μL
mALB	400μL	-----	-----	20μL	40μL
ASO	300μL	-----	-----	5μL	100μL
RF	300μL	-----	-----	5μL	100μL
Anti-CCP	350μL	-----	-----	10μL	50μL
D-Dimer	300μL	-----	-----	6μL	100μL

Test procedure



Step one

Put stirrer and buffer into the cuvette



Step two

Pipette the sample into the cuvette



Step three

Pipette anti-serum into the cuvette

Technical Specifications

Principle	Nephelometry
Throughput	40 samples/hour
Parameters	HS-CRP, CRP, HbA1c, mALB, D-Dimer, Anti-CCP, RF, ASO, CYS-C, IgA, IgM, IgG, C3, C4, etc. Can be extended more than 30 parameters
Sample type	Whole blood, serum, plasma, urine etc.
Light source	Diode laser, 650nm wavelength
Calibration	Magnetic card, make the result more accurately
Cuvette	Disposable cuvette
Testing channel	one channel
Reaction time	1.5~3min
Language	English, Russian
Display	5.6-inch color touch screen
Memory	100,000 results storage
Print	Auto and manual printing, thermal printer
Working temperature	10~30°C
Precision	CV≤5%
Power supply	AC 100-240V 50/60Hz
Size	275mm×278mm×145mm
Net weight	3.2kg
Support LIS and barcode	
NGSP certified	

