

★ Parameter

- Test method: 1 point end, 2 point end, Kinetics, Fixed-time, Coagulation, Turbidimetry.
- Test mode: Flow cell & cuvette.
- Optics: 8 standard wavelengths:340nm, 405nm, 450nm, 505nm, 546nm, 578nm, 630nm,670nm. 2 more for optional.
- Lamp house: Long-life tungsten halogen lamp, auto-sleep function.
- Temperature: 25, 30, 37°C and Room temperature. Multifunctional incubator.
- Flow cell capacity & optical path: 32ul, 10mm.
- Resolution: 0.0001 Abs.
- Photometric range: 0.0000-3.3000 Abs.
- Display: 7.0" TFT LCD with touch screen,800*480 pixels.
- Printer: Build-in thermal printer (57mm printer paper), Support external printer.
- CPU: ARM Cortex-A8, 800M Hz.
- Memory: DDR3 SDRAM: 512MB;
Flash: 256 MB;
Over 180 programs, Over 2 million results can be stored.
- Interface: Interface: USB x4, RS232 x1,VGA x1, Etherne(RJ45)t x1
USB port(host) for keyboard, mouse, printer, U disk, bar code reader etc.
USB port(slave) for PC connection(support PC software control function).
- Operational environment: Temperature: 15°C~35°C, Humidity: 35%~85%.
- Power requirement: Wide power supply AC 100-240V, 50/60 Hz.
- Dimension: 310*400*200mm(L*W*H)

