

Portable PH Meter

PH-26A



Features

- 2 points push-button calibration with auto-buffer recognition.
- Automatically calculates and displays electrode slopes that helps you decide whether to replace pH electrode.
- Selectable either temperature units between degrees Celsius ($^{\circ}\text{C}$) and degrees Fahrenheit ($^{\circ}\text{F}$).
- Automatic Temperature Compensation (ATC) ensures highly accurate measurements over the entire pH range.
- Manual temperature calibration provides accurate temperature values.
- Hold function freezes the current displayed values for easy viewing.
- Help message as a operational guide to helps you understand how to use meter.
- Setup menu allows user customizes temperature units, date and time to meet measurement requirements.
- Expanded memory stores and recalls up to 50 readings.
- Built-in real-time clock stamps stored data to meets GLP standards.

Specifications

Model	PH-26A
pH	
Range	-2.00~16.00pH
Accuracy	±0.01pH
Resolution	0.01pH
Calibration Points	2 points
Calibration Solutions	USA (pH4.01/7.00/10.01)
Temperature Compensation	0~100°C, 32~212°F
Compensation Mode	Manual or Automatic
mV	
Range	-1999~1999mV
Accuracy	±1mV
Resolution	1mV
Temperature	
Range	0~100°C, 32~212°F
Accuracy	±1°C
Resolution	0.1°C
Others	
Hold Function	Manual
Memory	Stores up to 50 data sets
Output	USB communication interface
Connector	BNC
Power Requirements	1×9V/800mA battery
Battery Life	Approximately 150 hours
Dimensions	185(L)×88(W)×32(H)mm
Weight	300g